

P3R PRESS TO CHECK COMPACT

P3R - FORCE™ F-3103

TECHNICAL SPECIFICATION

UNENCAPSULATED TWIN FILTERS FOR THE FORCE™ 8 HALF FACE MASK AND FORCE™ 10 FULL FACE MASK

RESPIRATORY PROTECTION

INSTRUCTIONS FOR USE

- Follow the instruction supplied to fit the filters to the mask in the correct way
- Align the arrows on the mask and filter. Twist the filter clockwise into the facemask inlet using the easy bayonet fitting
- Care must be taken to ensure that the correct filter type is selected for the work to be carried out
- If in doubt as to the type of filter required seek professional advice

PERFORMANCE

- When attached to a Force™ 8 Offers an assigned protection factor (APF) of 20 x Workplace Exposure Limit (WEL) against fine dusts, fibres, fumes and liquid aerosols*
- When attached to a Force™ 10 Offers an assigned protection factor (APF) of 40 x Workplace Exposure Limit (WEL) against fine dusts, fibres, fumes and liquid aerosols*
- The Nominal Protection Factor (NPF) -
Force 8 NPF = 50 Force 10 NPF = 1000

* The APF communicated is valid in the UK only and follows the recommendations of HSE and EN529 Annex C. For the Protection Factor applicable in your country, please contact the JSP Ltd Sales team

DIMENSIONS OF FILTER

- Height: 30mm
- Length: 120mm
- Width: 80mm
- Weight: 25g

PACKAGING DIMENSIONS

- Inner Packaging:** (Quantity: 1 Pair of filters Per Bag)
Height: 140mm Width: 35mm Length: 200mm Weight: 60g (Approx)
- Outer Packaging:** (Quantity: 10)
Height: 300mm Width: 200mm Length: 160mm Weight: 745g (Approx)

MATERIALS

- Filter Media: Non Woven Polypropylene Meltblown Fibres
- Frame: ABS
- Inhalation diaphragm: Synthetic rubber

CLEANING & MAINTENANCE

- Disposable filter, do not clean
- Store unopened packs in an airtight container, out of direct sunlight away from chemicals, abrasive substances and in a dry atmosphere



CONFORMITY

- Meets the requirements of EN143:2000+A1:2006
- EU Type Examination Certificate 677404, issued by BSI Product Certification
- Markings: P3 R, EN143:2006



LIMITATIONS OF USE

- Protection will only be offered if the filter is fitted correctly to an appropriate respirator
- The use by date is printed on the packaging
- The working life of the filter depends on many factors including work rate, airflow and concentration of any contaminant in the atmosphere
- The filter should be changed immediately if:
 - a. Breathing difficulties due to clogging are experienced
 - b. The filter becomes damaged
- Use in well ventilated areas only, which are not deficient in oxygen and do not contain explosive atmospheres
- Filter is designed to fit Force 8 and Force 10 only, do not modify to fit other JSP respirators or other manufacturers masks

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email technical@jpsafety.com



MANUFACTURING FOR SAFETY
WWW.JSPSAFETY.COM

UKSALES@JSPSAFETY.COM
TEL: +44 (0)1993 826050

