



18-3 COOL SUPRACOAT

- (EN) ULTRA THIN - DRY FEEL - CUT
 (DE) ULTRA DÜNN - TROCKENGEFÜHL - SCHNITTSCHUTZ
 (SE) ULTRATUNN - TORR KÄNSLA - SKÄRBESTÄNDIG
 (NL) ULTRA DUN - DROOG GEVOEL - SNIJBESTENDIG
 (FI) ERITTÄIN OHUT - KUIVA TUNNE - LEIKATA
 (NO) SUPERTYNN - TØR FØLELSE - KUTT
 (DK) ULTRA TYND - FØLES TØR - SKÆR
 (FR) ULTRA FIN - SENSATION SÊCHE - PROTECTION ANTI COUPE
 (IT) ULTRA SOTTILE - SENSAZIONE DI SECCHENZA - PROTEZIONE DAL TAGLIO
 (ES) ULTRAFINO - TACTO SECO - CORTE
 (PL) ULTRA CIENKIE - UCZUCIE SUCHOŚCI - PRZECIĘCIE
 (RO) ULTRA SUBTIRE - USCAT - ANTI TAIERE
 (AF) ULTRA DUN - DROE GEVOEL - SNY

EN388:2016



3X43C

- A:** ABRASION (1-4)
B: CUT (1-5)
C: TEAR (1-4)
D: PUNCTURE (1-4)
F: ISO CUT (A-F)
P: IMPACT PROTECTION

CE
CAT II

The glove should only be used in accordance with the pictograms printed on the glove. Make sure your mechanical requirements are fulfilled within the pictogram result.

Store the glove in its original packing in dark, cool and dry place. Inspect glove before use. Wash in 30 degrees with regular detergent. Gloves are not tested after washing. Use gloves within 3 years from purchase.

Glove is according to REGULATION (EU) 2016/425 & DIRECTIVE 89/686/EEC. Glove complies with EN388:2016 and EN420:2003+A1:2009.



Produced by: Y.Berger&Co AB, Ingela Gathenhielms Gata 3, SE 421 30 Västra Frölunda, Sweden.

For a copy of CE declaration or other details contact us through below:
 Phone: +46 31 75 10 850, Email: eureka@berger.se, Website: www.eurekasafety.se
 App: Eureka Safety Gloves









ART.NO: 18-3CSC

6 pairs / plastic bag - 60 pairs / carton



CUT RESISTANT - SCHNITTSCHUTZ





Suitable industries	
Abrasion	0 ————— 8000 cycles
Cut 	ISO 13997: C (A-F) ANSI:  (A1-A9)
Tear	0 ————— 75 N
Puncture	0 ————— 150 N
Impact 	✗
Needle  25 gg:	✗
Heat 	✗
Water & Oil 	✗
Grip  Dry: ————— High Wet/Oil: —————	
Breathing	Low ————— High



EN388
A: ABRASION (1-4)
B: CUT (1-5)
C: TEAR (1-4)
D: PUNCTURE (1-4)
F: ISO CUT (A-F)
P: IMPACT PROTECTION

ISO CUT (A-F)
A ≥ 2 N
B ≥ 5 N
C ≥ 10 N
D ≥ 15 N
E ≥ 22 N
F ≥ 30 N



Glove Purpose	Ultra thin cut resistant glove for dry/wet applications
Name & Number	18-3 Cool SupraCoat - 18-3CSC
Materials	HPPE, Fibreglass, Elastane, PU composite
Colour & Thickness	 Palm: 0,8 mm Back of hand: 0,5 mm
Size & Packing	 6 pairs / plastic bag 60 pairs / carton