

FS082

FIXO - NON ADJUSTABLE LANYARD

The **FALL SAFE® FS082 - FIXO NON ADJUSTABLE LANYARD** is a low stretch static kernmantle lanyard with high proportion of sheath to cover ratio wich provides improved abrasion protection. FS082 has heavy duty stitched ends for extra resistance.



EAN CODE	LENGTH (M)	WEIGHT (KG)
5605423730470	1,0	0,1
5605423730456	1,5	0,2
5605423730494	2,0	0,3

APPLICATIONS

Rescue | Riggers | Rope access



STANDARDS

CE EN354:2010

FS082 FIXO - NON ADJUSTABLE LANYARD

FEATURES



CONNECTOR COMBINATIONS



PHYSICAL PROPERTIES

Metal parts	N/A
Rope	Mamba negra 11mm
+ Available sizes	0.5M, 3M, 4M, 5M

OTHER INFORMATION

Device lifespan	10 years
Max. Load	<100 Kg
Inspection requirement	Yearly
Traceability	Serial Number/ QR Code
Manual Instructions	www.fallsafe-online.com +351 252 480 060

FS802 ZINC-PLATED STEEL OVAL

The **FALL SAFE® FS802 - ZINC PLATED STEEL OVAL** is a screw lock connector in zinc plated steel, with a 18 mm opening and a breaking strength of 25 kN.



EAN CODE	STRENGTH (kN)	OPENING (MM)	~WEIGHT (KG)	STANDARDS
5605423400113	25	18	0,162	CE EN362:2004-B EN12275:1998-H

APPLICATIONS

Telecom towers | Rope access | Roof works | Riggers | Rescue | Construction | Arborism



PHYSICAL PROPERTIES	
Material	Zinc plated steel
Closure	Screw lock
OTHER INFORMATION	
Device lifespan	Undefined*
Inspection requirement	Yearly
Traceability	Serial Number/ Batch number
Manual Instructions	www.fallsafe-online.com +351 252 480 060

*The product's lifetime is considered Undefined, when the products can be used until being rejected during the inspection.