

Datenblatt

IGNITE TRION



ALLGEMEIN

Art. no.: G-1131-XXL/5XL

EAN: 4030281222507

Standard: EN 358:1999
EN 361:2002

E-class number: 40-02-01-02

Customs no.: 63079098

Datenblatt

IGNITE TRION

The new high-performance full body harness for industry and trade is uncomplicated and very easy to buckle on. The harness scores with extremely flexible adjustments of belt straps that are passed through the thin but effective hip padding. Due to its asymmetric shape, the padding ensures that the buckle does not exert any pressure in the abdominal area. Ergonomic eyelets are perfectly folded in at the hip without interfering. They are unfolded for use and maintain their position after snapping - if necessary throughout the day. The innovative OKTALOCK click buckles made of stainless steel include new adjustment elements that eliminate undesirable loosening of the belt strap during movement and obviate the need for readjusting during work.

Functionality and ergonomics in abundance:

- asymmetric padding with integrated belt guide
- 4 buckles allow individual adjustments
- retaining eyelets fit the hip ergonomically

MERKMALE

Fall indicator

Shoulder or leg padding: yes

Belt strap coiler: yes

Hand-washing: 40 °C

Click buckles: yes

Lanyard Parking-Rings: yes

Max. service life: 6-8

Max. number of persons: 1

Max. rated load: 140 kg

Attachment Points:

dorsal attachment point, sternal attachment point, pole strap attachment point

Patent

Back support: yes

Temperaturbereich: von -35 °C bis 45 °C

Area of application:

Construction / Roofer / Carpenter, Facade / Window Cleaning, High Rack, Metal Construction, Mobile Work Platforms, Power Supplies / - Transmission / Telecommunications, Scaffolding, Wind Energy / Offshore Industry

MAßE

Size:	XXL/5XL
Waist size:	900-1400mm
Weight:	2.318

MATERIAL

Material:

Aluminium, Polyester, Steel

Webbing material: PES

Sternal attachment point material:

AL

Pole strap attachment point material:

AL

Dorsal attachment point material:

AL

Material Click buckle: V2A