

DATASHEET

SCOUT



GENERAL

Art.Nr:	L-0828-15	Standards:	EN 353-2:2002, RFU PPE-R/11.075
GTIN:	4030281023555	Net weight:	2.40 kg
E-class number:	40-02-01-07	Gross weight:	2.40 kg
Customs tariff number:	84799070		

DATASHEET

SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

FEATURES

Application areas:	Various
Fallindicator:	Yes
Colour:	White, Red
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

DIMENSIONS

Rope length:	15.00 m
length_lanyard:	15.00 m
Rope diameter:	11.00 mm
Lanyard rope diameter:	11.00 mm

MATERIAL

Material:	Polyamide, Steel, Stainless Steel
-----------	-----------------------------------

DATASHEET

SCOUT



GENERAL

Art.Nr:	L-0828-20	Standards:	EN 353-2:2002,RFU PPE-R/11.075
GTIN:	4030281023562	Net weight:	2.81 kg
E-class number:	40-02-01-07	Gross weight:	2.81 kg
Customs tariff number:	84799070		

DATASHEET

SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

FEATURES

Application areas:	Various
Fallindicator:	Yes
Colour:	White, Red
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

DIMENSIONS

Rope length:	20.00 m
length_lanyard:	20.00 m
Rope diameter:	11.00 mm
Lanyard rope diameter:	11.00 mm

MATERIAL

Material:	Polyamide, Steel, Stainless Steel
-----------	-----------------------------------

DATASHEET

SCOUT



GENERAL

Art.Nr:	L-0828-5	Standards:	EN 353-2:2002,RFU PPE-R/11.075
GTIN:	4030281023531	Net weight:	1.58 kg
E-class number:	40-02-01-07	Gross weight:	1.58 kg
Customs tariff number:	84799070		

DATASHEET

SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

FEATURES

Application areas:	Various
Fallindicator:	Yes
Colour:	White, Red
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

DIMENSIONS

Rope length:	5.00 m
length_lanyard:	5.00 m
Rope diameter:	11.00 mm
Lanyard rope diameter:	11.00 mm

MATERIAL

Material:	Polyamide, Steel, Stainless Steel
-----------	-----------------------------------

DATASHEET

SCOUT



GENERAL

Art.Nr:	L-0828-10	Standards:	EN 353-2:2002,RFU PPE-R/11.075
GTIN:	4030281023548	Net weight:	1.99 kg
E-class number:	40-02-01-07	Gross weight:	1.99 kg
Customs tariff number:	84799070		

DATASHEET

SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

FEATURES

Application areas:	Various
Fallindicator:	Yes
Colour:	White, Red
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

DIMENSIONS

Rope length:	10.00 m
length_lanyard:	10.00 m
Rope diameter:	11.00 mm
Lanyard rope diameter:	11.00 mm

MATERIAL

Material:	Polyamide, Steel, Stainless Steel
-----------	-----------------------------------