

# DATASHEET

## SCOUT



### GENERAL

Art.Nr:	L-0845-50	Standards:	EN 353-2:2002,RFU PPE-R/11.075
GTIN:	4030281310617	Net weight:	5.32 kg
E-class number:	40-02-01-07	Gross weight:	5.32 kg
Customs tariff number:	84799070		

# DATASHEET

## SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

### FEATURES

Application areas: lithium\_ion, Roofers, Facades cleaning, Flat roof construction, High Rack storage, Mobile Work Platforms, Off Shore Industry, Rescue, Emergency, Route construction, RBA rigging, Shaft, Steelwork, Telco energy

Fallindicator:	Yes
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

### DIMENSIONS

Rope diameter:	11.00 mm
Lanyard rope diameter:	11.00 mm

### MATERIAL

Material:	Polyamide, Steel, Stainless Steel
-----------	-----------------------------------

# DATASHEET

## SCOUT



### GENERAL

Art.Nr:	L-0845-75	Standards:	EN 353-2:2002,RFU PPE-R/11.075
GTIN:	4030281310624	Net weight:	7.37 kg
E-class number:	40-02-01-07	Gross weight:	7.37 kg
Customs tariff number:	84799070		

# DATASHEET

## SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

### FEATURES

Application areas: lithium\_ion, Roofers, Facades cleaning, Flat roof construction, High Rack storage, Mobile Work Platforms, Off Shore Industry, Rescue, Emergency, Route construction, RBA rigging, Shaft, Steelwork, Telco energy

Fallindicator:	Yes
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

### DIMENSIONS

Rope diameter:	11.00 mm
Lanyard rope diameter:	11.00 mm

### MATERIAL

Material:	Polyamide, Steel, Stainless Steel
-----------	-----------------------------------

# DATASHEET

## SCOUT



### GENERAL

Art.Nr:	L-0845-100	Standards:	EN 353-2:2002,RFU PPE-R/11.075
GTIN:	4030281310631	Net weight:	9.42 kg
E-class number:	40-02-01-07	Gross weight:	9.42 kg
Customs tariff number:	84799070		

# DATASHEET

## SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

### FEATURES

Application areas: lithium\_ion, Roofers, Facades cleaning, Flat roof construction, High Rack storage, Mobile Work Platforms, Off Shore Industry, Rescue, Emergency, Route construction, RBA rigging, Shaft, Steelwork, Telco energy

Fallindicator:	Yes
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

### DIMENSIONS

Rope diameter:	11.00 mm
Lanyard rope diameter:	11.00 mm

### MATERIAL

Material:	Polyamide, Steel, Stainless Steel
-----------	-----------------------------------

# DATASHEET

## SCOUT



### GENERAL

Art.Nr:	L-0845-5	Standards:	EN 353-2:2002,RFU PPE-R/11.075
GTIN:	4030281029519	Net weight:	1.63 kg
E-class number:	40-02-01-07	Gross weight:	1.63 kg
Customs tariff number:	84799070		

# DATASHEET

## SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

### FEATURES

Application areas: Route construction, lithium\_ion, Off Shore Industry, Rescue, Telco energy, High Rack storage, Steelwork, Emergency, RBA rigging, Working in confined spaces, Elevator construction, Roofers, Shaft, Flat roof construction

Fallindicator:	Yes
Colour:	Red, White
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

### DIMENSIONS

Rope length:	5.00 m
Rope diameter:	11.00 mm
Lanyard rope diameter:	11.00 mm

### MATERIAL

Material:	Polyamide, Steel, Stainless Steel
-----------	-----------------------------------



# DATASHEET

## SCOUT



### GENERAL

Art.Nr:	L-0845-10	Standards:	EN 353-2:2002,RFU PPE-R/11.075
GTIN:	4030281029526	Net weight:	2.04 kg
E-class number:	40-02-01-07	Gross weight:	2.04 kg
Customs tariff number:	84799070		

# DATASHEET

## SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

### FEATURES

Application areas: Route construction, lithium\_ion, Off Shore Industry, Rescue, Telco energy, High Rack storage, Steelwork, Emergency, RBA rigging, Working in confined spaces, Elevator construction, Roofers, Shaft, Flat roof construction

Fallindicator:	Yes
Colour:	Red, White
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

### DIMENSIONS

Rope length:	10.00 m
Rope diameter:	11.00 mm
Lanyard rope diameter:	11.00 mm

### MATERIAL

Material:	Polyamide, Steel, Stainless Steel
-----------	-----------------------------------

# DATASHEET

## SCOUT



### GENERAL

Art.Nr:	L-0845-15	Standards:	EN 353-2:2002,RFU PPE-R/11.075
GTIN:	4030281029533	Net weight:	2.45 kg
E-class number:	40-02-01-07	Gross weight:	2.45 kg
Customs tariff number:	84799070		

# DATASHEET

## SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

### FEATURES

Application areas: Route construction, lithium\_ion, Off Shore Industry, Rescue, Telco energy, High Rack storage, Steelwork, Emergency, RBA rigging, Working in confined spaces, Elevator construction, Scaffolding, Roofers, Shaft, Flat roof construction

Fallindicator:	Yes
Colour:	Red, White
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

### DIMENSIONS

Rope length:	15.00 m
Rope diameter:	11.00 mm
Lanyard rope diameter:	11.00 mm

### MATERIAL

Material:	Polyamide, Steel, Stainless Steel
-----------	-----------------------------------

# DATASHEET

## SCOUT



### GENERAL

Art.Nr:	L-0845-20	Standards:	EN 353-2:2002, RFU PPE-R/11.075
GTIN:	4030281029540	Net weight:	2.86 kg
E-class number:	40-02-01-07	Gross weight:	2.86 kg
Customs tariff number:	84799070		

# DATASHEET

## SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

### FEATURES

Application areas: Route construction, lithium\_ion, Off Shore Industry, Rescue, Telco energy, High Rack storage, Steelwork, Emergency, RBA rigging, Working in confined spaces, Elevator construction, Scaffolding, Roofers, Shaft, Flat roof construction

Fallindicator: Yes

Colour: Red, White

Hand wash: 40 °C

Edge approved: Yes

Maximum lifetime: 10 years

Maximum temperature: 45 °C

Minimum temperature: -35 °C

### DIMENSIONS

Rope length: 20.00 m

Rope diameter: 11.00 mm

Lanyard rope diameter: 11.00 mm

### MATERIAL

Material: Polyamide, Steel, Stainless Steel

# DATASHEET

## SCOUT



### GENERAL

Art.Nr:	L-0845-30	Standards:	EN 353-2:2002,RFU PPE-R/11.075
GTIN:	4030281310600	Net weight:	3.68 kg
E-class number:	40-02-01-07	Gross weight:	3.68 kg
Customs tariff number:	84799070		

# DATASHEET

## SCOUT

The universally applicable SCOUT fall arrester with integrated strap fall arrester offers a large range of motion due to the rope length (5 m, 10 m, 15 m, 20 m) . It is approved for user weights up to 150 kilograms and, due to its edge suitability, can be used both for vertical ascents and for horizontal work on fall edges. The fall arrester slides along the rope with very low friction, both during ascent and descent. Thanks to an integrated panic function, the SCOUT locks immediately in the event of a fall and enables reliable positioning of the user. The intuitive, compact fall arrester is made of stainless steel and can therefore withstand the toughest conditions. SCOUT is certified according to EN 353-2.

- Flexible work thanks to large range of motion
- Universally applicable: horizontal and vertical suitability.
- Reliable positioning thanks to panic function.

### FEATURES

Application areas: lithium\_ion, Roofers, Facades cleaning, Flat roof construction, High Rack storage, Mobile Work Platforms, Off Shore Industry, Rescue, Emergency, Route construction, RBA rigging, Shaft, Steelwork, Telco energy

Fallindicator:	Yes
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum temperature:	-35 °C

### DIMENSIONS

Rope diameter:	11.00 mm
Lanyard rope diameter:	11.00 mm

### MATERIAL

Material:	Polyamide, Steel, Stainless Steel
-----------	-----------------------------------