

DATASHEET ANCHOR CABLE 8MM



GENERAL

Art.Nr:	L-0002-1	ANSI Z359.18:2017 3.2.1.1,CEN/TS Standards: 16415:2017-11,EN 354:2010,EN 795-B:	
GTIN:	4030281003793		
			2012
E-class number:	40-02-01-90	Net weight:	0.66 kg
Customs tariff	7312102000001		
number: 7		Gross weight:	0.66 kg

www.skylotec.com I Datenblatt, 18.10.23



DATASHEET

ANCHOR CABLE 8MM

The ANCHOR CABLE steel cable is ideal for setting up heavy-duty anchor points

around structural elements and in the strand. It is made of galvanised steel

cable (8mm) and is cut and abrasion resistant. A transparent protective plastic cover protects against wear during use. Connecting elements according to EN 362 can be attached through the end eyelets. The test load is 22.2 kN. - cut and abrasion resistant - with transparent protective cover made of wear-resistant plastic

FEATURES

Application areas:	Emergency, RBA rigging, Telco energy, Arborists
Fallindicator:	No
Colour:	Silver
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	37.60 kN
DIMENSIONS	
Rope length:	1.00 m
length_lanyard:	1.00 m
MATERIAL	
Material:	Steel

Material:

www.skylotec.com I Datenblatt, 18.10.23



DATASHEET ANCHOR CABLE 8MM



GENERAL

Art.Nr:	L-0002-2	ANSI Z359.18:2017 3.2.1.1,CEN/TS Standards: 16415:2017-11,EN 354:2010,EN 795-B:	
GTIN:	4030281015000		
	40-02-01-90		2012
E-class number:		Net weight:	0.87 kg
Customs tariff			
number: 73121020	Gross weight:	0.87 kg	



DATASHEET

ANCHOR CABLE 8MM

The ANCHOR CABLE steel cable is ideal for setting up heavy-duty anchor points

around structural elements and in the strand. It is made of galvanised steel

cable (8mm) and is cut and abrasion resistant. A transparent protective plastic cover protects against wear during use. Connecting elements according to EN 362 can be attached through the end eyelets. The test load is 22.2 kN. - cut and abrasion resistant - with transparent protective cover made of wear-resistant plastic

FEATURES

Material:

Application areas:	Emergency, RBA rigging, Telco energy, Arborists
Fallindicator:	No
Colour:	Silver
Edge approved:	No
Maximum lifetime:	10 years
Minimum tensile strength:	37.60 kN
DIMENSIONS	
Rope length:	2.00 m
length_lanyard:	2.00 m
MATERIAL	

Steel