

Data sheet
PEANUT I



GENERAL

Art. no.: HSG-021-1,8-3

EAN: 4030281181934

Standard:

DIN 19427:2017
EN 360:2002
GS-PS-12:2019
RFU PPE-
R/11.060:2018
RFU PPE-
R/11.085:2020
RFU PPE-
R/11.124:2020

E-class number: 40-02-01-03

Customs no.: 84798997

Data sheet

PEANUT I

The compact connecting device PEANUT I with FS90 ST karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The karabiner with an opening width of 59 mm can be used variably and is extremely robust. The fastener is suitable for edges and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 1.8 m long arm makes PEANUT I ideal for securing in aerial work platforms. Due to the spring-loaded webbing retraction, the person remains safely on the platform even in case of a catapult effect. A red indicator shows when the strap fall arrester has been triggered and provides additional safety. The PEANUT I also serves to secure the stand.

FEATURES

Colour:	grey / black
Fall indicator	
Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	135 KG
Patent	
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND
Area of application:	
Confined Spaces, Facade / Window Cleaning	

DIMENSIONS

Size:	1,8m
Weight:	1,94 kg

HARDWARE

Carabiner on anchoring point side:
FS 90 ST

Carabiner on belt side: KOBRA TRI

MATERIAL

Material:
Polyester, Polyamide, Steel