

Data sheet

PEANUT I f. Platforms



GENERAL

Art. no.:	HSG-021-1,8-8	E-class number:	40-02-01-03
EAN:	4030281197720	Customs no.:	84798997
Standard:	DIN 19427:2017 EN 360:2002 GS-PS-12:2019 RFU PPE- R/11.060:2018 RFU PPE- R/11.085:2020 RFU PPE- R/11.124:2020		

Data sheet

PEANUT I f. Platforms

The compact connecting device PEANUT I with the KOBRA TRI karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The small steel trilock karabiner with a breaking load of 45 kN and an opening width of 22 mm is characterised above all by its robustness. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 1.8 m long arm makes PEANUT I ideal for securing in aerial work platforms. Due to the spring-loaded webbing retraction, the person remains safely on the platform even in case of a catapult effect. A red indicator shows when the strap fall arrester has been triggered and provides additional safety. The PEANUT I also serves to secure the stand.

FEATURES

Colour:	grey / black
Fall indicator	
Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	135 KG
Patent	
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND
Area of application:	Facade / Window Cleaning

DIMENSIONS

Size:	1,8m
Weight:	1,74 kg

HARDWARE

Carabiner on anchoring point side:
KOBRA TRI

Carabiner on belt side: KOBRA TRI

MATERIAL

Material:
Polyester, Polyamide, Steel