

Data sheet
PEANUT I



GENERAL

Art. no.:	HSG-021-2,5-7	E-class number:	40-02-01-03
EAN:	4030281182016	Customs no.:	84798997
Standard:	EN 360:2002 GS-PS-12:2019 RFU PPE- R/11.060:2018 RFU PPE- R/11.085:2020 RFU PPE- R/11.124:2020		

Data sheet

PEANUT I

The compact connecting device PEANUT I with the FS64 AL GR karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The FS64 AL GR with an opening width of 64 mm is light and yet very robust with a reinforced gate. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 2.5 m long arm makes PEANUT I ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Colour:	grey / black
Fall indicator	
Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	135 KG
Patent	
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND
Area of application:	Scaffolding

DIMENSIONS

Size:	2,5m
Weight:	1,93 kg

HARDWARE

Carabiner on anchoring point side:
FS 64 ALU

Carabiner on belt side: KOBRA AL TRI

MATERIAL

Material:
Polyester, Polyamide, Steel