

Data sheet
PEANUT Y



GENERAL

Art. no.: HSG-022-2,5-1

EAN: 4030281183440

Standard: EN 360:2002
GS-PS-12:2019
RFU PPE-
R/11.060:2018
RFU PPE-
R/11.085:2020
RFU PPE-
R/11.124:2020

E-class number: 40-02-01-03

Customs no.: 84798997

Data sheet

PEANUT Y

The compact connecting device PEANUT Y with FS90 ALU karabiner convinces with its self-retracting arms, which do not restrict the working radius and ensure that the fall height is extremely low. The all-rounder carabiner with an opening width of 60 mm is suitable for almost all structures and can be opened easily. The lanyard is perfectly suited for continuous, mutual securing - even at lower heights. The PEANUT Y is edge-suitable and therefore also serves for horizontal securing. The product contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. Due to the 2.5 m long arms, the PEANUT Y is ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Colour:	orange / black
Fall indicator	
Suitable for edges:	yes
Max. service life:	10 Years
Max. number of persons:	1
Rated load:	135 KG
Patent	
Temperature:	from 45 °C to -35 °C
Suspension element:	BAND
Area of application:	
Construction / Roofer / Carpenter, Scaffolding	

DIMENSIONS

Size:	2,5m
Weight:	2,86 kg

HARDWARE

Carabiner on anchoring point side:
FS 90 ALU

Carabiner on belt side: STAK TRI

MATERIAL

Material:
Polyester, Polyamide, Aluminium