

Data sheet

Lory PRO



GENERAL

Art. no.:	A-041	E-class number:	40-02-01-06
EAN:	4030281280163	Customs no.:	84798997
Standard:	DIN EN 12841-C:2006 DIN EN 15151-1:2012 DIN EN 341-2A:2011 EN 795/B:2012		

Data sheet

Lory PRO

LORY is a robust descender and belay device. Its various application areas make the Lory your reliable companion for rope access and rescue (abseiling up to 225 kg load). LORY is used for work positioning, as a restraining device at roofs or slab edges, as a temporary anchor or for fall arrest in flexible cable systems. With LORY, the belaying person can easily feed and take rope. When using the device correctly, it blocks automatically in case of a fall. The LORY PRO model with its unimpeded movement of the cam is the ideal device for industrial purposes. It is equipped with a descent handle that ensures secured and controlled abseiling. The double-stop function blocks if the handle is pulled overly in panic and provides extra safety.

EN 341: max./min. rated load: 30 - 180 kg;
max. descent height: 190 m; rope diameter: 11 mm

EN 12841-C: max. rated load: 225 kg; rope diameter: 10-12 mm

EN 795: rope diameter: 10.5 / 11 mm

ANSI Z359.4-2013

FEATURES

Colour:	black / orange
Abseiling height:	190,00 m
Max. service life:	30 Years
Temperature:	from 60 °C to -20 °C
Area of application:	Arborists, Fire brigade / Rescue / Special Forces, Rope Access / Rigging, Rope Courses, Wind Energy / Offshore Industry

DIMENSIONS

Weight:	0,37 kg
---------	---------

MATERIAL

Material:	Aluminium
-----------	-----------