

Data sheet

INCEPTOR GRX



GENERAL

Art. no.:	BE-390-12
EAN:	4030281269625
Standard:	meets partly EN 397:2012+A1:2012

E-class number:	40-01-11-01
Customs no.:	65061010

Data sheet

INCEPTOR GRX

The INCEPTOR GRX is redefining the concept of safety. The specially-designed EPS thorax and PC/ABS shell absorb particularly high impact energies, both in the vertex area and at the side. The largest possible ventilation holes and ergonomic EPS thorax ensure exceptional wearing comfort. The INCEPTOR GRX's neck strap allows continuous width adjustment from 54 to 63 cm. The chin strap is equipped with a Fidlock buckle: the ergonomic magnetic closure is easy to open and close with its secure and self-actuated engagement.

The gear rack, multiple helmet clips and Euroslots allow accessories such as headlamps, hearing protection and neck guards to be attached. All of the padding inside can be interchanged, cleaned or replaced. Not least, the INCEPTOR GRX impresses with its striking and straightforward contours.

INCEPTOR GRX - EN 12492:2012, meets partly EN 397:2012

FEATURES

Temperature:
from -30 °C to +50 °C

Area of application:
Arborists, Construction / Roofer / Carpenter, High Rack, Mobile Work Platforms, Rope Access / Rigging, Scaffolding, Wind Energy / Offshore Industry

DIMENSIONS

Size:	54-63cm
Weight:	0,45 kg

MATERIAL

Material:
Polycarbonat, Acrylnitril-Butadien-Styrol,
Expanded Polystyrene

Data sheet

INCEPTOR GRX



GENERAL

Art. no.:	BE-390-01
EAN:	4030281269489
Standard:	meets partly EN 397:2012+A1:2012

E-class number:	40-01-11-01
Customs no.:	65061010

Data sheet

INCEPTOR GRX

The INCEPTOR GRX is redefining the concept of safety. The specially-designed EPS thorax and PC/ABS shell absorb particularly high impact energies, both in the vertex area and at the side. The largest possible ventilation holes and ergonomic EPS thorax ensure exceptional wearing comfort. The INCEPTOR GRX's neck strap allows continuous width adjustment from 54 to 63 cm. The chin strap is equipped with a Fidlock buckle: the ergonomic magnetic closure is easy to open and close with its secure and self-actuated engagement.

The gear rack, multiple helmet clips and Euroslots allow accessories such as headlamps, hearing protection and neck guards to be attached. All of the padding inside can be interchanged, cleaned or replaced. Not least, the INCEPTOR GRX impresses with its striking and straightforward contours.

INCEPTOR GRX - EN 12492:2012, meets partly EN 397:2012

FEATURES

Temperature:
from -30 °C to +50 °C

Area of application:
Arborists, Construction / Roofer / Carpenter, Fire brigade / Rescue / Special Forces, High Rack, Mobile Work Platforms, Rope Access / Rigging, Wind Energy / Offshore Industry

DIMENSIONS

Size:	54-63cm
Weight:	0,45 kg

MATERIAL

Material:
Polycarbonat, Acrylnitril-Butadien-Styrol,
Expanded Polystyrene

Data sheet

INCEPTOR GRX



GENERAL

Art. no.:	BE-390-07
EAN:	4030281269618
Standard:	meets partly EN 397:2012+A1:2012

E-class number:	40-01-11-01
Customs no.:	65061010

Data sheet

INCEPTOR GRX

The INCEPTOR GRX is redefining the concept of safety. The specially-designed EPS thorax and PC/ABS shell absorb particularly high impact energies, both in the vertex area and at the side. The largest possible ventilation holes and ergonomic EPS thorax ensure exceptional wearing comfort. The INCEPTOR GRX's neck strap allows continuous width adjustment from 54 to 63 cm. The chin strap is equipped with a Fidlock buckle: the ergonomic magnetic closure is easy to open and close with its secure and self-actuated engagement.

The gear rack, multiple helmet clips and Euroslots allow accessories such as headlamps, hearing protection and neck guards to be attached. All of the padding inside can be interchanged, cleaned or replaced. Not least, the INCEPTOR GRX impresses with its striking and straightforward contours.

INCEPTOR GRX - EN 12492:2012, meets partly EN 397:2012

FEATURES

Temperature:
from -30 °C to +50 °C

Area of application:
Arborists, Construction / Roofer / Carpenter, Fire brigade / Rescue / Special Forces, High Rack, Mobile Work Platforms, Rope Access / Rigging, Scaffolding, Wind Energy / Offshore Industry

DIMENSIONS

Size:	54-63cm
Weight:	0,45 kg

MATERIAL

Material:
Polycarbonat, Acrylnitril-Butadien-Styrol, Expanded Polystyrene

Data sheet

INCEPTOR GRX



GENERAL

Art. no.:	BE-390-13
EAN:	4030281285403
Standard:	MEETS PARTL.EN397:2012+A1:2012

E-class number:	40-01-11-01
Customs no.:	65061010

Data sheet

INCEPTOR GRX

The INCEPTOR GRX is redefining the concept of safety. The specially-designed EPS thorax and PC/ABS shell absorb particularly high impact energies, both in the vertex area and at the side. The largest possible ventilation holes and ergonomic EPS thorax ensure exceptional wearing comfort. The INCEPTOR GRX's neck strap allows continuous width adjustment from 54 to 63 cm. The chin strap is equipped with a Fidlock buckle: the ergonomic magnetic closure is easy to open and close with its secure and self-actuated engagement.

The gear rack, multiple helmet clips and Euroslots allow accessories such as headlamps, hearing protection and neck guards to be attached. All of the padding inside can be interchanged, cleaned or replaced. Not least, the INCEPTOR GRX impresses with its striking and straightforward contours.

INCEPTOR GRX - EN 12492:2012, meets partly EN 397:2012

FEATURES

Temperature: from -30 °C to 50 °C

Area of application:

Arborists, Construction / Roofer / Carpenter, Fire brigade / Rescue / Special Forces, High Rack, Mobile Work Platforms, Rope Access / Rigging, Scaffolding, Wind Energy / Offshore Industry

DIMENSIONS

Size: 54-63cm

Weight: 0,45 kg

MATERIAL

Material:

Polycarbonat, Acrylnitril-Butadien-Styrol, Expanded Polystyrene

Data sheet

INCEPTOR GRX



GENERAL

Art. no.:	BE-390-13
EAN:	4030281285403
Standard:	MEETS PARTL.EN397:2012+A1:2012

E-class number:	40-01-11-01
Customs no.:	65061010

Data sheet

INCEPTOR GRX

The INCEPTOR GRX is redefining the concept of safety. The specially-designed EPS thorax and PC/ABS shell absorb particularly high impact energies, both in the vertex area and at the side. The largest possible ventilation holes and ergonomic EPS thorax ensure exceptional wearing comfort. The INCEPTOR GRX's neck strap allows continuous width adjustment from 54 to 63 cm. The chin strap is equipped with a Fidlock buckle: the ergonomic magnetic closure is easy to open and close with its secure and self-actuated engagement.

The gear rack, multiple helmet clips and Euroslots allow accessories such as headlamps, hearing protection and neck guards to be attached. All of the padding inside can be interchanged, cleaned or replaced. Not least, the INCEPTOR GRX impresses with its striking and straightforward contours.

INCEPTOR GRX - EN 12492:2012, meets partly EN 397:2012

FEATURES

Temperature: from -30 °C to 50 °C

Area of application:

Arborists, Construction / Roofer / Carpenter, Fire brigade / Rescue / Special Forces, High Rack, Mobile Work Platforms, Rope Access / Rigging, Scaffolding, Wind Energy / Offshore Industry

DIMENSIONS

Size: 54-63cm

Weight: 0,45 kg

MATERIAL

Material:

Polycarbonat, Acrylnitril-Butadien-Styrol, Expanded Polystyrene

Data sheet

INCEPTOR GRX



GENERAL

Art. no.:	BE-390-03
EAN:	4030281299288
Standard:	MEETS PARTL.EN397:2012+A1:2012

E-class number:	40-01-11-01
Customs no.:	65061010

Data sheet

INCEPTOR GRX

The INCEPTOR GRX is redefining the concept of safety. The specially-designed EPS thorax and PC/ABS shell absorb particularly high impact energies, both in the vertex area and at the side. The largest possible ventilation holes and ergonomic EPS thorax ensure exceptional wearing comfort. The INCEPTOR GRX's neck strap allows continuous width adjustment from 54 to 63 cm. The chin strap is equipped with a Fidlock buckle: the ergonomic magnetic closure is easy to open and close with its secure and self-actuated engagement.

The gear rack, multiple helmet clips and Euroslots allow accessories such as headlamps, hearing protection and neck guards to be attached. All of the padding inside can be interchanged, cleaned or replaced. Not least, the INCEPTOR GRX impresses with its striking and straightforward contours.

FEATURES

Max. number of persons: 1

Temperature: from 50 °C to -30 °C

Area of application:

Arborists, Construction / Roofer / Carpenter, Fire brigade / Rescue / Special Forces, High Rack, Rope Access / Rigging, Wind Energy / Offshore Industry

DIMENSIONS

Size: 54-63cm

Weight: 0,45 kg

MATERIAL

Material:

Polycarbonat, Acrylnitril-Butadien-Styrol,
Expanded Polystyrene